

Single Phase, TEFC, Foot Mounted

1/12 thru 15 Hp

NEMA 42 thru 256T

Applications: Compressors, pumps, fans, farm equipment, conveyors, material handling equipment, machine tools and others.

Features: Heavy gauge steel frames and a heavy duty base seam welded to the frame, ball bearings, a "Snap Action" starting switch and gasketed conduit box and capacitor cover.



Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)	
1/12	1800	42	L3351	296	K	9.56	15	44	115/230	1	3, 30	
	3600	42	L3352	303	K	9.56	15	45	115/230	1.3	3, 30	
1/8	1800	42	L3353	308	K	9.56	16	47	115/230	1.6	3, 30	
	3600	42	L3354	318	K	9.56	16	52	115/230	1.6	3, 30	
1/6	1800	42	L3355	336	K	9.56	18	51	115/230	1.8	3, 30	
		48	L3400	335	K	10.73	18	49	115/230	1.9	3, 30	
	1200	48	L3401	472	K	10.73	23	47	115/230	2.3	3, 30	
1/4	3600	42	L3356	340	K	9.56	18	57	115/230	2	3, 30	
	1800	48	EL3403	420	K	11.35	24	74	115/230	1.3	1, 65	
		48	L3403	344	K	10.73	20	55	115/230	2.5	3, 30	
		48	L3403M	394	K	10.73	20	55	115/230	2.5	3, 30	
	1200	48	L3404	503	K	11.35	26	48	115/230	3.2	3, 30	
1/3	3600	48	EL3405	402	K	11.35	28	72	115/208-230	1.6	30, 65	
		48	L3405	313	K	10.73	20	55	115/208-230	3	3, 30	
	1800	48	L3406	365	K	10.73	22	60	115/230	3	3, 30	
		48	L3406M	414	K	10.73	22	60	115/230	3	3, 30	
		56	EL3501	464	K	11.97	28	77	115/230	1.6	1, 65	
		56	L3501	353	K	11.35	22	60	115/230	3	3, 30	
	1200	48	L3501M	414	K	11.35	22	60	115/230	3	3, 30	
		48	L3407	553	K	11.35	27	54	115/230	3.7	3, 30	
	1/2	3600	48	L3502	553	K	11.97	29	54	115/230	3.7	3, 30
			48	L3408	354	K	10.73	24	66	115/230	3.5	3, 30
1800		56	EL3503	455	K	11.97	24	68	115/230	2.5	65	
		56	L3503	354	K	11.35	22	66	115/230	3.5	3, 30	
		48	L3409	405	K	11.35	26	68	115/230	3.7	3, 30	
		48	L3409M	487	K	11.35	27	68	115/230	3.7	3, 30	
		56	EL3504	547	K	11.97	32	78.5	115/230	2.3	1, 65	
		56	L3504	414	K	11.35	27	68	115/230	3.7	3, 30	
		56	L3504A	495	K	11.97	27	68	115/230	3.7	3, 30	
		56	L3504M	487	K	11.97	27	68	115/230	3.7	3, 30	
1200	56/56H	L3505	784	K	12.93	42	59	115/230	4	3, 30, 36		
3/4	3600	56	EL3506	512	K	11.97	29	72	115/230	3.9	65	
		56	L3506	399	K	11.97	29	66	115/230	4.8	3, 30	
	1800	56	EL3507	666	K	13.25	44	82.5	115/208-230	3.2	1, 65	
		56	L3507	477	K	12.47	35	72	115/230	4.2	30, 65	
		56	L3507A	598	K	12.47	34	74	115/230	4.1	30, 65	
		56	L3507M	572	K	12.47	34	74	115/230	4.1	30, 65	
	1200	56/56H	L3508	907	K	12.93	43	68	115/230	5	2, 30, 36, 65	
		143T	L3508T	893	L1	13.29	44	68	115/230	5	2, 30, 65	

(a) See notes on inside back flap.

General Information

Single Phase Motors

General Purpose Industrial Motors

Severe Duty Motors

Large AC Motors

Washdown Duty Motors

Explosion Proof Motors

Pump Motors

Light Industrial/Commercial Motors

HVAC Motors

Single Phase, TEFC, Foot Mounted

Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)	
1	3600	56/56H	EL3509	591	K	12.93	39	74	115/208-230	4.7	65	
		56/56H	L3509	462	K	12.93	37	68	115/230	5.9	3, 30, 36	
		56/56H	L3509M	522	K	12.93	40	66	115/230	6	3, 36	
	1800	56/56H	L3510A	672	K	12.93	40	67	115/230	6.5	3, 30, 36	
		56/56H	L3510M	649	K	12.93	40	67	115/230	6.5	3, 30, 36	
		56H	EL3510	765	K	13.81	47	82.5	115/230	4.3	1, 36, 65	
		56H	L3510	541	K	12.93	40	68	115/230	6.4	3, 30, 36	
		143T	L3510T	552	L1	13.29	41	68	115/230	6.4	3, 30	
		143T	L3510TM	649	L1	13.31	41	67	115/230	6.5	3, 30	
		182	L3601	996	L1	14.31	54	72	115/230	6	3, 30	
1200	184	L3607	1,590	L1	15.69	74	67	115/230	7	3, 30		
1 1/2	3600	56/56H	L3513	619	K	12.93	41	70	115/230	8	3, 30, 36	
		56/56H	L3513M	708	K	12.93	45	70	115/230	7.5	2, 3, 36	
		143T	L3513T	607	L1	13.31	41	70	115/230	8	3, 30	
	1800	56/56H	L3514	625	K	13.81	49	75.5	115/230	8	30, 36, 65	
		56/56H	L3514A	797	K	13.81	48	75.5	115/230	8	2, 36, 65	
		56/56H	L3514M	733	K	13.81	50	75.5	115/208-230	8	2, 36, 65	
		56H	EL3514	871	K	15.18	57	84	115/230	6.3	1, 36, 65	
		145T	EL3514T	871	L1	15.55	59	84	115/230	6.3	1, 65	
		145T	L3514T	634	L1	13.30	40	78.5	115/208-230	7	30, 65	
		145T	L3514TM	733	L1	14.17	50	75.5	115/208-230	8	2, 65	
	1200	184	L3603	1,085	L1	15.69	66	70	115/230	9.5	3, 30	
	2	3600	184T	L3613T	1,657	L1	16.56	78	73	115/230	8.2	1, 30, 65
			56/56H	L3515	790	K	13.81	51	74	115/230	11.5	1, 3, 30, 36
			56/56H	L3515M	827	K	13.81	52	74	115/230	11.5	2, 3, 36
145T			L3515T	797	L1	14.19	54	74	115/230	11.5	1, 3, 30	
1800		145T	EL3515T	1,022	L1	14.18	56	77	115/208-230	8.3	65	
		56HZ	L3516TM	1,043	K	13.31	46	82.5	208-230	8.1	1, 57	
		145T	L3516T	1,013	L1	14.18	52	78	115/230	8.6	1, 65	
		182T	L3605T	905	L1	16.56	67	75.5	115/230	11.5	3, 30	
		182T	L3605TM	1,104	L1	16.56	74	75	115/230	11	2, 3	
		182T	EL3605T	1,191	L1	16.56	72	82.5	115/230	8.8	1, 65	
		184	L3605	1,214	L1	15.69	66	75.5	115/230	11.5	3, 30	
1200		184	L3605M	1,301	L1	15.69	66	75.5	115/230	11.5	3, 30	
3		3600	215	L3703	2,626	L1	17.51	113	80	115/230	9.4	2, 30, 65
			182T	EL3606T	1,112	L1	16.56	80	82	115/230	12.4	2, 65
	182T		L3606T	934	L1	16.56	73	76	115/230	14.5	1, 3, 30	
	184		L3606	1,713	L1	15.69	74	76	115/230	14.5	1, 3, 30	
	1800	184T	EL3609T	1,390	L1	18.06	90	85.5	230	11.8	1, 65	
		184T	L3609T	1,065	L1	16.56	79	78	115/230	14	2, 20, 30, 65	
		184T	L3609TM	1,152	L1	16.54	95	78	115/230	14.5	2, 20	
		215	L3705	2,070	L1	17.51	116	80	115/230	14	30, 65	
		1200	215	L3706	3,153	L1	17.51	101	82.5	115/230	14	1, 30, 65
	5	3600	184T	EL3608T	1,533	L1	18.06	93	85	230	19.4	2, 20, 65
184T			L3608T	1,285	L1	18.06	89	83	230	19.5	2, 20, 65	
184T			L3608TM	1,326	L1	18.05	92	83	230	19.5	2, 20	
1800		184T	EL3612T	1,658	L1	18.06	100	86.5	230	19.1	2, 20, 65	
		184T	L3612TM	1,339	L1	18.05	100	80	230	23	2, 20	
		213T	L3708T	1,271	L1	19.02	100	84	230	20.5	1, 30, 65	
		213T	L3708TM	1,493	L1	19.02	138	82	230	21.5	2, 65	
7 1/2	3600	215	L3708	2,117	L1	18.64	100	84	230	20.5	1, 30, 65	
10	3600	213T	L3709T	1,655	L1	17.89	126	83	230	33	2, 30, 65	
	1800	215T	L3710T	1,679	L1	19.02	116	86.5	230	29	2, 20, 30, 65	
15	3600	215T	L3711T	2,029	L1	19.02	147	82	230	40	2, 20, 65	
	1800	215T	L3712T	2,060	L1	20.52	158	86.5	230	38	2, 20, 65	
15	1800	254T	L1177T	5,867	L1	23.28	322	86.5	230	60	2, 20, 65	
		256T	L3912T	5,269	L1	24.56	288	86.5	208-230	58	30	

(a) See notes on inside back flap.

■ Cast Iron Frame

General Information

Single Phase Motors

General Purpose Industrial Motors

Severe Duty Motors

Large AC Motors

Washdown Duty Motors

Explosion Proof Motors

Pump Motors

Light Industrial/Commercial Motors

HVAC Motors

Single Phase, TEFC, C-Face, No Drip Cover

1/6 thru 10 Hp

NEMA 56C thru 215TC

Applications: Pumps, fans, conveyors, machine tools, gear reducers and other applications requiring a NEMA C-face motor.

Features: Pressure cast aluminum end plates with ribbed design for rigidity. Ball bearings with a locked drive end bearing, heavy-gauge steel frame, and gasketed conduit box and capacitor cover.



Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
C-Face, Foot Mounted											
1/4	1800	56C	CL3403	363	K	11.35	19	55	115/230	2.5	3
1/3	3600	56C	CL3405	362	K	11.35	21	55	115/208-230	3	3
	1800	56C	CL3501	379	K	11.35	23	60	115/230	3	3, 30
1/2	3600	56C	CL3503	380	K	11.35	24	66	115/230	3.5	3, 30
	1800	56C	CL3504	443	K	11.35	28	66	115/230	3.7	3, 30
3/4	3600	56C	CL3506	423	K	11.97	29	66	115/230	4.8	3, 30
	1800	56C	CL3507	529	K	12.47	35	72	115/230	4.2	30, 65
1	3600	56C	CL3509	489	K	12.25	37	68	115/230	5.9	3, 30
	1800	56C	CL3510	597	K	13.25	40	68	115/230	6.4	3, 30
1 1/2	3600	56C	CL3513	633	K	13.25	44	70	115/230	7.5	3, 30
	1800	56C	CL3514	708	K	14.12	49	75.5	115/230	8	30, 65
2	3600	56C	CL3515	816	K	14.12	54	74	115/230	11.5	1, 3, 30
		145TC	CL3515T	823	L1	14.19	54	74	115/230	11.5	1, 3, 30
3	1800	145TC	CL3516TM	1,052	L1	14.16	52	78	208-230	8.3	1
	1800	184TC	CL3619TM	1,368	L1	16.54	81	81.5	230	13.2	2, 20
5	3600	184TC	CL3608TM	1,482	L1	18.05	102	83	230	19.5	2, 20
	1800	184TC	CL3612TM	1,434	L1	18.05	101	80	230	23	2, 20
10	3600	215TC	CL3711T	2,409	L1	19.75	167	82	230	40	2, 20
	1800	213TC	CL3712T	2,438	L1	21.25	171	86.5	230	38	2, 20
C-Face, Footless											
1/6	1800	56C	KL3400	353	K	11.35	18	49	115/230	1.9	3, 30
	1200	56C	KL3401	494	K	11.35	23	47	115/230	2.3	3, 30
1/4	1800	56C	KL3403	363	K	11.35	20	55	115/230	2.5	3, 30
	3600	56C	KL3405	335	K	11.35	21	55	115/208-230	3	3
1/3	1800	56C	VL3501	372	K	11.35	22	60	115/230	3	3, 30
	3600	56C	VL3503	376	K	11.35	23	66	115/230	3.5	3, 30
1/2	1800	56C	VL3504	435	K	11.35	27	68	110/220	3.7	3, 30
	1200	56C	VL3505	805	K	13.25	41	59	115/230	4	3, 30
3/4	3600	56C	VL3506	418	K	11.97	29	66	115/230	4.8	3, 30
		56C	VL3506A	462	K	11.97	30	66	115/230	4.8	3
1	1800	56C	VL3507	498	K	12.47	34	66	115/230	4.2	30, 65
	1200	56C	VL3508	926	K	13.25	43	68	115/230	5	2, 30, 65
1	3600	56C	VL3509	481	K	12.25	37	68	115/230	5.9	3, 30
		56C	VL3509A	526	K	13.25	40	68	110/220	6	3
1 1/2	1800	56C	VL3510	571	K	13.25	39	68	115/230	6.4	3, 30
		143TC	VL3510T	571	L1	13.29	41	68	115/230	6.4	3, 30
2	3600	56C	VL3513	626	K	13.25	41	70	115/230	8	3, 30
		143TC	VL3513T	665	L1	13.31	41	70	115/230	8	3, 30
3	1800	56C	VL3514	647	K	14.12	47	75.5	115/230	8	30, 65
		145TC	VL3514T	654	L1	14.17	50	75.5	115/230	8	30, 65
2	3600	56C	VL3515	801	K	14.12	51	74	115/230	11.5	1, 3, 30
		143TC	VL3515T	816	L1	14.19	19	74	115/230	11.5	1, 3, 30
3	1800	182TC	VL3605T	1,157	L1	16.55	66	75.5	115/230	11.5	3, 30
		184C	VL3605	1,309	L1	15.68	65	75.5	115/230	11.5	3, 30
3	3600	182TC	VL3606T	1,291	L1	16.55	74	76	115/230	14.5	1, 3, 30
	1800	184TC	VL3609T	1,366	L1	16.55	79	78	115/230	14	2, 20, 30, 65

(a) See notes on inside back flap.

Single Phase,
ODP, Foot Mounted

1/6 thru 10 Hp

NEMA 48 thru 215T



Applications: Compressors, pumps, conveyors, machine tools, air handling, and others.

Features: Copper windings, dynamically balanced rotors, ball bearings, heavy-gauge steel frames, and other industrial quality features.

Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)	
1/6	1800	48	L1200	279	K	9.13	18	49	115/230	1.9	30	
	1200	48	L1201	427	K	9.38	23	47	115/230	2.3	30	
1/4	1800	48	EL1203	365	K	9.76	23	74	115/230	1.3	1, 65	
		48	L1203	284	K	9.13	22	59.5	115/230	2.2	30	
		48	L1203M	326	K	9.13	20	55	115/230	2.5	30	
	1200	48	L1204	456	K	9.75	25	48	115/230	3.2	30	
		56	L1300	475	K	10.13	26	48	115/230	3.2	30	
		48	EL1205	333	K	9.76	26	72	115/208-230	1.6	65	
1/3	3600	48	L1205	268	K	9.13	20	55	115/208-230	3	30	
		48	L1206	326	K	9.13	29	60	115/230	3	30	
	1800	48	L1206M	367	K	9.13	22	60	115/230	3	30	
		56	EL1301	431	K	10.13	26	77	115/230	1.6	1, 65	
		56	L1301	329	K	9.51	22	60	115/230	3	30	
		56	L1301M	386	K	9.51	22	60	115/230	3	30	
		1200	48	L1207	487	K	10.63	28	54	115/230	3.7	30
			56	L1302	487	K	11.01	29	54	115/230	3.7	30
	1/2	3600	48	L1208	296	K	9.13	22	57	115/230	3.7	30
			56	EL1303	367	K	10.13	23	68	115/230	2.5	65
56			L1303	296	K	9.51	21	66	115/230	3.5	30	
1800		48	L1209	410	K	9.75	26	68	115/230	3.7	30	
		48	L1209M	455	K	9.38	24	62	115/230	4.2	30	
		56	EL1304	494	K	11.00	31	78.5	115/230	2.3	1, 65	
		56	L1304	365	K	10.13	28	68	115/230	3.7	30	
		56	L1304A	434	K	9.76	25	62	115/230	4.2	30	
		56	L1304M	455	K	9.76	25	62	115/230	4.2	30	
1200		56/56H	L1305	732	K	11.75	38	62	115/230	4.1	30, 36	
3/4		3600	56	EL1306	447	K	11.00	37	72	115/230	3.9	65
			56	L1306	362	K	12.85	26	72	115/230	4.7	30
	56		L1306A	380	K	11.75	31	69	115/230	5.5		
	1800	56	EL1307	608	K	12.06	39	84	115/208-230	3.3	1, 65	
		56	L1307	450	K	11.51	32	68	115/230	5.1	30	
		56	L1307A	528	K	11.51	32	68	115/230	5.1	30	
		56	L1307M	541	K	11.51	32	68	115/230	5.1	30	
	1200	56/56H	L1308	824	K	11.75	42	68	115/230	5	30, 36, 65	
1	3600	56	EL1309	470	K	11.00	32	74	115/208-230	5.1	65	
		56	L1309	379	K	11.01	31	65	115/230	7.5	30	
		56	L1309A	404	K	11.01	31	70	115/230	6.6		
	1800	56/56H	L1318	538	K	11.75	42	67	115/230	6.2	30, 36	
		56/56H	L1318M	586	K	11.75	42	67	115/230	6.2	2, 36	
		56	EL1310	663	K	12.94	43	84	115/208-230	4.3	1, 65	
		56	L1310	492	K	11.07	34	66	115/230	6.7	30	
		56H	L1310M	629	K	11.75	35	66	115/230	6.7	30, 36	
		143T	L1318T	561	L1	12.12	41	67	115/230	6.2	30	
		143T	L1318TM	586	L1	12.12	41	67	115/230	6.2	2	
		182	L1401	799	L1	12.75	51	70	115/230	7	30	
182	L1401M	867	L1	12.75	49	70	115/230	7				
1200	184	L1407	1,401	L1	14.13	63	65	115/230	8	30		

(a) See notes on inside back flap.

General Information

Single Phase Motors

General Purpose Industrial Motors

Severe Duty Motors

Large AC Motors

Washdown Duty Motors

Explosion Proof Motors

Pump Motors

Light Industrial/Commercial Motors

HVAC Motors

Single Phase, ODP, Foot Mounted

Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)	
1 1/2	3600	56/56H	L1313A	556	K	11.75	40	68	115/230	9	30, 36	
		56H	EL1313	658	K	12.25	37	80	115/208-230	6.2	65	
		56H	L1313	532	K	11.75	35	77	115/230	6.4	30, 36, 65	
		143T	L1313T	532	L1	11.12	36	70	115/230	8.9	30	
	1800	56/56H	L1319	634	K	11.75	42	68	115/230	9	30, 36	
		56/56H	L1319M	707	K	11.75	42	68	115/230	9	36	
		56H	EL1319	868	K	14.00	50	85.5	115/208-230	6.3	1, 36, 65	
		143T	EL1319T	900	L1	13.00	52	85.5	115/208-230	6.3	1, 65	
		145T	L1319T	599	L1	12.12	41	68	115/230	9	30	
		145T	L1321T	719	L1	13.00	50	70	115/230	10.5	30	
		145T	L1321TM	780	L1	13.00	50	70	115/208-230	10.5		
		184	L1403	892	L1	12.75	56	68	115/230	9.5	30	
184	L1403M	945	L1	12.75	56	68	115/230	9.5				
2	3600	56/56H	L1317	707	K	11.75	43	70	115/230	13	30, 36	
		56/56H	L1317A	727	K	11.75	44	70	115/230	12	30, 36	
		56H	EL1317	875	K	11.75	51	75.5	115/230	9		
		145T	L1320T	758	L1	12.12	48	71	115/230	11.5	30, 65	
	1800	145T	L1322T	733	L1	13.00	50	75.5	115/208-230	10.2	65	
		145T	L1322TM	798	L1	13.00	50	78.5	115/230	9.2	65	
		182T	EL1405T	1,014	L1	15.87	68	82.5	115/230	8.8	1, 65	
		182T	L1405T	752	L1	15.00	65	71	115/230	12	30	
		184	L1405	936	L1	14.13	64	71	115/230	12	30	
		213	L1502	1,607	L1	14.32	82	69	115/230	12.5	30	
		1200	215	L1503	2,188	L1	15.94	101	68	115/230	14	30
		3	3600	182T	EL1406T	1,068	L1	15.00	74	81	115/230	12.3
182T	L1406T			862	L1	15.00	65	78	115/230	14	30	
1800	184T		EL1408T	1,062	L1	16.50	84	85.5	208-230	11.2	1, 65	
	184T		L1408T	814	L1	15.00	77	78	115/230	16	30, 65	
	184T		L1408TM	958	L1	15.00	78	78	115/230	16		
	215		L1505	1,781	L1	15.94	105	75	115/230	18	30	
1200	215		L1506	2,557	L1	15.94	111	75	115/230	16	30, 65	
5	3600		184T	EL1409T	1,268	L1	15.00	77	81.5	230	20	65
		184T	L1409T	1,026	L1	15.00	79	75	230	23	30	
	1800	184T	EL1410T	1,213	L1	18.00	127	86.5	230	19.1	1, 65	
		184T	L1410T	962	LS	16.50	84	82.5	230	23	1, 30, 65	
		184T	L1410TM	1,165	L1	16.50	90	82.5	230	23	1, 30	
		184T	L1430T	883	L1	16.55	84	84	230	20.6	1, 30, 65	
		184T	L1430TM	1,165	L1	16.55	84	80	230	24	1, 30, 65	
		213T	L1508T	1,271	L1	16.32	103	77	230	27		
7 1/2	3600	213T	L1509T	1,585	L1	18.37	98	82.5	230	30	1, 30, 65	
	1800	215T	L1510T	1,379	L1	17.45	142	85.5	230	31	30, 65	
10	3600	215T	L1511T	1,999	L1	17.45	144	83	230	46	1, 30	
	1800	215T	L1512T	2,013	L1	17.45	123	85.5	230	39	2, 65	

(a) See notes on inside back flap.

General Information

Single Phase Motors

General Purpose Industrial Motors

Severe Duty Motors

Large AC Motors

Washdown Duty Motors

Explosion Proof Motors

Pump Motors

Light Industrial/Commercial Motors

HVAC Motors

**Single Phase,
ODP, C-Face**

1/6 thru 5 Hp

NEMA 56C thru 184TC



Applications: Pumps, fans, conveyors, machine tools, gear reducers and other applications requiring a NEMA C-face motor.

Features: Pressure cast aluminum end plates with ribbed design for rigidity. Ball bearings with a locked drive end bearing, heavy-gauge steel frame.

Hp	RPM	NEMA Frame	Catalog Number	List Price	Mult. Sym.	"C" Dim.	Aprx. Wt. (lb)	Full Load Efficiency	Voltage	Full Load Amps	Notes (a)
C-Face, Foot Mounted, No Drip Cover											
1/3	1800	56C	CL1301	369	K	10.10	23	60	115/230	3	30
1/2	3600	56C	CL1303	327	K	10.06	24	66	115/230	3.5	30
	1800	56C	CL1304	420	K	10.35	25	62	115/230	4.2	30
3/4	1800	56C	CL1307	481	K	12.06	34	68	115/230	5.1	30
1	1800	56C	CL1310	553	K	11.06	34	66	115/230	6.7	30
3	1800	184TC	CL1408TM	1,012	L1	15.00	87	78	115/230	16	
5	1800	184TC	CL1410TM	1,220	L1	16.50	99	82.5	230	23	1, 30
C-Face, Footless, Drip Cover											
1/6	1800	56C	KL1200	299	K	11.22	18	49	115/230	1.9	30
1/4	1800	56C	KL1203	304	K	11.22	20	55	115/230	2.5	30
1/3	3600	56C	KL1205	290	K	11.22	21	55	115/208-230	3	30
		56C	KL1205A	296	K	11.35	21	55	115/230	3	30
	1800	56C	VL1301	350	K	11.22	22	60	115/230	3	30
1/2	3600	56C	VL1303	318	K	11.22	23	66	115/230	3.5	30
	1800	56C	VL1304	385	K	11.47	24	62	115/230	4.2	30
	1200	56C	VL1305	752	K	13.24	39	62	115/230	4.1	30
3/4	3600	56C	VL1306	380	K	12.85	27	72	115/230	4.7	30
	1800	56C	VL1307	470	K	13.22	33	68	115/230	5.1	30
	1200	56C	VL1308	843	K	13.24	43	68	115/230	5	30
1	3600	56C	VL1309	400	K	12.72	32	65	115/230	7.5	30
	1800	56C	VL1310	512	K	12.24	35	66	115/230	6.7	30
		56C	VL1318	556	K	13.24	42	67	115/230	6.2	30
1 1/2	3600	56C	VL1313	553	K	12.73	32	77	115/230	6.4	30
	1800	56C	VL1319	654	K	13.24	42	68	115/230	9	30
		145TC	VL1321T	740	L1	14.17	50	70	115/230	10.5	30
2	3600	56C	VL1317	727	K	13.24	43	70	115/230	13	30
	1800	145TC	VL1322T	754	L1	14.18	50	75.5	115/208-230	10.2	65
3	3600	182TC	VL1406T	916	L1	15.18	61	75.5	115/230	13.6	30, 65
	1800	184TC	VL1408T	927	L1	16.55	80	78	115/230	16	30, 65

(a) See notes on inside back flap.

General Information

Single Phase Motors

General Purpose Industrial Motors

Severe Duty Motors

Large AC Motors

Washdown Duty Motors

Explosion Proof Motors

Pump Motors

Light Industrial/Commercial Motors

HVAC Motors