

# DuPont™ Krytox®

## LUBRICATION POINTS FOR AUTOMOTIVE BEARING APPLICATIONS

**EXTREME CONDITIONS. EXTREME PERFORMANCE.**


### High Performance Lubricants that Work in Demanding Real-Life Applications

Reliable high-performance DuPont fluoropolymer lubricants can stand up to even extreme conditions. DuPont™ Krytox® oils and greases have proven scientific and technical properties to help solve the most critical issues in the automotive industry. Superior product performance, lower overall maintenance systems cost, and a lower environmental footprint help to meet rising consumer expectations. For automotive manufacturers, this provides the opportunity to offer extended warranties and enjoy improved productivity through reduced component failure.

DuPont™ Krytox® oils and greases are based on perfluoropolyether (PFPE) oils. These synthetic fluorinated lubricants are used in extreme conditions such as continuous high temperatures up to 288°C (550°F), and higher temperatures for shorter periods, depending on product grade limits. DuPont™ Krytox® oils and greases are exceptionally safe, reliable, and offer environmental benefits as well as longer lubricant life. These oils and greases will not burn or support combustion even in 100% liquid or gaseous oxygen, nor will they degrade or break down in the presence of aggressive chemicals. In automotive applications, Krytox® oils and greases deliver low temperature starting performance, while maintaining efficacy at higher temperatures. These oils and greases can increase service life of critical components, allowing them to run more quietly and last longer, for superior, reliable performance.

### Vehicle Applications

See the illustration below for the many applications where Krytox® has been proven effective. The bearing applications are shown in bold type.



The miracles of science™



## DuPont™ Krytox® — Products for the Automotive Industry

Several grades of DuPont™ Krytox® oil and grease are suitable for automotive use, depending on the application type and temperature range encountered. The table below lists the most common grades currently being used. More detailed data is available on the web at [www.krytox.com](http://www.krytox.com).

| DuPont™ Krytox® Greases                                   | Viscosity, cSt | Temperature Range, °C |
|---|----------------|-----------------------|
| GPL 204, GPL 214, GPL 224, GPL 294, GPL 2E4, XP2A4        | 60             | -51 to +179           |
| AUT 2E45, AUT 2245, AUT 2045, AUT 2A45                    | 100            | -40 to +200           |
| GPL 205, GPL 215, GPL 225, GPL 295, GPL 2E5, XP2A5, XP2C5 | 160            | -36 to +210           |

### Proven Applications

#### Fan Clutch

A thermostatically-controlled fan clutch typically drives the cooling fan. The bearings that support the drive shaft for this clutch regularly experience high temperatures. If these bearings wear and begin to fail, the cooling fan runs less efficiently. When this occurs, the engine can overheat, and any resistance in fan clutch rotation can drain valuable power from the engine's drive shaft, further reducing overall performance. DuPont™ Krytox® lubricants have low volatility and high viscosity, providing long-life and excellent lubrication to the fan clutch bearing under these high temperature conditions.

#### Alternator

The alternator is usually belt-driven by the engine, and supplies electricity to basic automobile functions (headlights, radio, etc.) while recharging the car battery. As the electricity is being generated, the alternators and hence the bearings get very hot. Standard lubricants volatilize in the extreme high temperature environment of the alternator, leading to alternator bearing failure. As the bearings wear and begin to fail, they can increase the alternator's resistance to rotation. This reduces the alternator's performance, and robs performance from the rest of the automobile. Perhaps more critically, if the alternator bearings fail, the alternator will fail and the vehicle will stop running. The higher output alternators used in today's vehicles generate a tremendous amount of heat, demanding the advanced and reliable, heat-stability and performance of DuPont™ Krytox® greases.

#### Clutch Pilot Bearings

The pilot bearings support the clutch-end of the transmission shaft. If the lubricant in the pilot bearing fails, the transmission itself will fail. Pilot bearings lubricated with DuPont™ Krytox® high performance lubricants will last longer and perform better than those lubricated with other synthetic lubricants due to the high-load capability and chemical inertness of Krytox® products.

#### Cooling Fan

To maximize performance, an automobile's engine must run at its optimal temperature (typically around 93°C [200°F]), which is controlled by the cooling system. One component of the system is the cooling fan, which blows air through the radiator, removing excess heat. Failure in the cooling fan's bearings leads to failure of the fan, which will eventually result in overheating of the engine. The sintered bearings used in cooling fans often fail in two ways: either the lubricant volatilizes, or it degrades through oxidation. The use of DuPont™ Krytox® prevents both of these modes of failure due to its low volatility and unsurpassed resistance to oxidation.

#### Heavy Duty Truck Automatic Clutch

In many heavy duty trucks, the engines have a much lower RPM upper limit. In order to prevent the engine from being destroyed, an automatic clutch is used. When the set maximum RPM limit is reached, the automatic clutch disengages and notifies the driver to shift gears. This both prevents engine damage and increases ease of operation. The bearings present in the clutch are critical to its operation and must receive adequate lubrication in order to work properly. Lubricating with DuPont™ Krytox® mid-range viscosity and low volatility lubricants reduces the chance that the bearings will fail with the frequent gear-shifting and high loads experienced throughout the extended driving life of these trucks.



**For more information or for technical assistance, please call us  
at 1-800-424-7502 or contact us at [krytox@usa.dupont.com](mailto:krytox@usa.dupont.com).**

**For international sales and support contacts, visit us at  
[www.lubricants.dupont.com](http://www.lubricants.dupont.com)**

Copyright © 2009 DuPont. The DuPont Oval Logo, DuPont™, The miracles of science™ and Krytox® are registered trademarks or trademarks of E.I. du Pont de Nemours and Company or its affiliates. All rights reserved.

K-20547 (02/09) Printed in the U.S.A.

The information set forth herein is furnished free of charge and based on technical data that DuPont believes to be reliable. It is intended for use by persons having technical skill and at their own discretion and risk. Because conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information. Nothing herein is to be taken as license to operate under or a recommendation to infringe any patents.



***The miracles of science™***