



DuPont™ Krytox® Premium Performance Gearbox Greases

PRODUCT INFORMATION

DuPont Performance Lubricants has developed a series of greases specifically designed to lubricate and protect high temperature gearbox gears, bearings, and seals. Krytox® fluoropolymer greases provide excellent lubrication and will not oxidize in the most demanding high temperature environments, even in applications with operating temperatures up to approximately 270 °C. Use of Krytox® gearbox grease will help eliminate bearing and gear failures resulting from lubricant oxidation, lead to longer seal life and extend gearbox life. In many applications, Krytox® gearbox grease will last the life of the gearbox, greatly reducing or eliminating the need for maintenance and relubrication. When compared to oil-lubricated systems, use of Krytox® grease can also significantly help reduce lubricant leakage related to seal failure.

Krytox® gearbox greases are available in various base oil viscosities to provide the best performance for your given environment. There are currently two grades of premium performance gearbox grease, DuPont™ Krytox® GB M0 and

GB H0, which are semi-fluid lubricants specifically designed for enclosed gearbox lubrication. As many gearbox designs utilize bearings that are not lubricated by the internal lubricant reservoir and require periodic relubrication (and this grease is often forced past the bearing seals into the reservoir), grades GB A2 and C2 have been added to the line to limit cross contamination of the internal grease with a non-compatible bearing grease.

Please consult with Krytox® Technical Service to determine if one of these grades is right for your application, or if an additional grade is required.

Krytox® greases are made from clear, colorless fluorinated, synthetic oils that are non-reactive, non-flammable, safe in harsh environments, long lasting and compatible with all seal materials. Krytox® is a perfluoropolyether based polymer composed of fluorine, oxygen and carbon. No hydrogen is present in the molecule, resulting in exceptional stability and non-flammability.

Gearbox Grease Grade	GB M0	GB H0	GB A2	GB C2
NLGI Grade	0	0	2	2
Penetration, ASTM D217	355–385	355–385	265–295	265–295
Thickener Chemistry	PTFE	PTFE	PTFE	PTFE
Dropping Point, °C	>290	>290	>290	>290
Base Oil Viscosity, 40 °C	100	500	100	500
Estimated Useful Temperature Range, °C	-40 – 210	-4 – 270	-40 – 210	-4 – 270
Appearance	Grey, Creamy	Grey, Creamy	Grey, Creamy	Grey, Creamy
Specific Gravity	2.1	2.1	2.1	2.1

DuPont Performance Lubricants

Extreme conditions. Extreme performance.

For more information or for technical assistance, please call **1-800-424-7502** or contact us at krytox@usa.dupont.com

For international sales and support contacts, visit us at www.lubricants.dupont.com

Copyright © 2012 DuPont. The DuPont Oval Logo, DuPont™, The miracles of science™ and Krytox® are registered trademarks or trademarks of E.I. du Pont de Nemours and Company or its affiliates. All rights reserved.

K-17005-5 (03/12) Printed in the U.S.A.

The information set forth herein is furnished free of charge and based on technical data that DuPont believes to be reliable. It is intended for use by persons having technical skill and at their own discretion and risk. Because conditions of use are outside our control, DuPont makes no warranties, express or implied, and assumes no liability in connection with any use of this information. Nothing herein is to be taken as license to operate under or a recommendation to infringe any patents or trademarks.



The miracles of science™